



un secolo di idee per l'agricoltura



FVM

Dati Tecnici - Technical data



ALLESTIMENTO DI SERIE

- Dischi spessore 4,5 mm (Ø 560) o 6 mm (Ø 610) lisci anteriori e dentati posteriori (salvo diversa indicazione) • Inclinazione idraulica sezioni dischi • N° 8 supporti di tipo oscillante su cuscinetto • Asse porta dischi in acciaio esagonale da 36 • Raschifango registrabili e sostituibili singolarmente • Ruote 26 x 12.00 - 12

ACCESSORI

- Dischetto coprisolco • Staffe salva-supperto • Raschifango rinforzati



STANDARD OUTFIT

- Front smooth discs and rear notched discs (unless specified differently) • Hydraulic adjustment of the angle of the discs gangs • 8 supports with a unique design that permits the bearing to oscillate in any direction • 36 mm hex steel disc shaft • Individually replaceable and adjustable mud scrapers • Wheels 26 x 12.00 - 12

ACCESSORIES

- Furrow covering disc • Shield for the supports • Heavy duty mud scrapers









Dischetto Coprisolco
Furrow covering disc



Staffa Salva Supporto
Shield for the supports



Modello	Codice	N° 	 Ø mm	 mm	HP 	 cm	 Kg
FVM 823 18-56	M1FR8543	18	560	230	70	204	1125
FVM 823 18-61	M1FR8533	18	610	230	75	204	1190
FVM 823 20-56	M1FR8544	20	560	230	75	227	1165
FVM 823 20-61	M1FR8534	20	610	230	85	227	1235
FVM 823 22-56	M1FR8545	22	560	230	85	250	1205
FVM 823 22-61	M1FR8535	22	610	230	90	250	1280
FVM 823 24-56	M1FR8546	24	560	230	90	273	1245
FVM 823 24-61	M1FR8536	24	610	230	90	273	1325



A.SPEDO & FIGLI SRL

Via Bovazecchino, 674

45021 BADIA POLESINE (RO) - Italy

Tel. (+39) 0425 51471 - 0425 52205 Fax (+39) 0425 590650

www.spedo.eu - info@spedo.eu